

Europäisches Patentamt
European Patent Office
Office européen des brevets

I D S



(11) EP 1 312 720 A1

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
21.05.2003 Bulletin 2003/21

(51) Int Cl.7: E02F 3/36

(21) Application number: 01204404.6

(22) Date of filing: 19.11.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Mantovani, Alberto
41034 Finale Emilia (Modena) (IT)

(74) Representative: Gotra, Stefano
BUGNION S.p.A.
Via Emilia Est 25
41100 Modena (IT)


(71) Applicant: Mantovanibenne S.r.l.
41037 Mirandola (MO) (IT)

(54) Rapid tool coupling device

(57) In the rapid tool coupling device for digger tools, a tool is provided with two pivots operating as means for hooking-up, the tool comprising: a body (1) provided with mobile hooks (2) which are actuated to achieve stable removable couplings with at least one of the two pivots.

ots. At least one plurality of first supports (5) and at least one second support (6), are predisposed to couple with a corresponding plurality of pairs of the two pivots, which pairs comprise a first pivot (3) and a second pivot (4), and which can be removably fixed to the body (1).

Fig. 1



EP 1 312 720 A1

Description

[0001] Specifically, though not exclusively, the invention is usefully applied for all tools, in particular buckets, which are hooked up using two parallel pivots predisposed on the bucket, which are used for hooking up to a rapid-coupling device provided on the end of the digger manoeuvring arm.

[0002] Numerous manufacturers of diggers and digger tools exist on the market.

[0003] Also numerous are the different types of attachments, which are generally dimensioned and configured so that only tools having complementary attachments can be hooked up to them.

[0004] All this constitutes a serious limitation to tool use, as it is not easy to obtain a full range of tools, buckets or otherwise, for a single digger.

[0005] The main aim of the present invention is to provide a rapid coupling device which obviates the limitations of the prior art with simple solution.

[0006] These aims and advantages and others besides are all achieved by the present invention, as it is characterised in the appended claims.

[0007] Further characteristics and advantages of the present invention will better emerge from the detailed description that follows of an embodiment of the invention, illustrated by way of example and not to be considered limiting in the accompanying figures of the drawings, in which:

figure 1 is a partially-sectioned schematic side view according to line III-III of figure 3;

figure 2 is a side view of a detail of figure 1;

figure 3 is a schematic side view from the left of figure 2;

figure 4 is an exploded side view of a detail of figure 2.

[0008] With reference to the figures of the drawings, 1 denotes in its entirety the body of a rapid coupling device for digger tools, of the type in which the tool, in the figures denoted by 7, is provided with a first pivot 3 and a second pivot 4 which together constitute means by which the tool will be hooked up.

[0009] The body 1 is provided with blocking devices comprising mobile hooks 2 which achieve stable but removable couplings with at least one of the two pivots 3 and 4, and especially with the second pivot 4.

[0010] The hooking-up is achieved by coupling the pivots 3 and 4 in special coupling seatings 50 and 60 especially afforded in first supports 5 and second supports 6 which are removably fixed on the body 1.

[0011] Each body 1 is predisposed to receive a pair of first supports 5 and a pair of second supports 6. The supports of each pair are positioned in such a way that the surfaces of the seatings 50 and 60 are aligned so as to be able to couple respectively with the first pivots 3 and the second pivots 4.

[0012] The first supports 5 and the second supports 6 are mounted easily removably on the body 1, and can be constrained thereon in predetermined positions.

[0013] For each tool 7, i.e. for each hooking-up system constituted by a first pivot 3 and a second pivot 4, a set formed by a pair of first supports 5 and a pair of second supports 6 is provided. Thus by mounting the right supports 5 and 6 on the body 1, the desired tool can be fixed thereon.

[0014] It is not certain that in each case the above-described conditions will arise. It is perfectly possible that even with a plurality of different tools 7 it will be necessary only to have a corresponding plurality of first supports 5 but only one second support 6 - or vice versa. In this case the first pivots 3 (or second pivots 4) of a plurality of tools 7, not very different in type one from another, can be coupled in a single seating 50 (or 60) of a first support 5 (or second support 6), the same seating being suitable for all of the tools 7, while the geometrical and dimensional difference in the attachment is present only in the seatings 60 (or 50) of the second supports 6 (or first supports).

[0015] More generally, there is a plurality of first supports 5 which corresponds to a plurality of second supports 6, which are predisposed to couple with a corresponding plurality of the first pivots 3 and the second pivots 4, and which can in all cases be removably fixed to the body 1.

[0016] The stability of the couplings is ensured by the fact that a single pair, formed by a first pivot 3 and a second pivot 4 on a single tool 7, is coupled with another pair constituted by first supports 5 and second supports 6.

[0017] The relative constraint between the first supports 5 and the body 1 is removable and uses the same references on the body for all the first supports 5.

[0018] The relative constraint between the second supports 6 and the body 1 is removable and uses the same references on the body for all the second supports 6.

[0019] In particular, the references are constituted by holes 11 made on the body 1 for allowing any first support 5 to be bolted thereon, and by other holes 12, also made on the body 1 for allowing any second support 6 to be bolted thereon.

[0020] The adaptation of the tool attachment to a specific tool 7 is made easy by making the attachment itself as a sort of modular structure which comprises a body 1, provided with mobile hooks 2 which in the illustrated embodiment are moved by a pneumatic cylinder 8, and a double plurality of pairs of first supports 5 and second supports 6 which are easily mountable on, and dismountable from, the body 1.

[0021] A special combination of first supports 5 and second supports 6 corresponds to each tool. When mounted on the body 1, by using the predetermined references, a rapid attachment can simply be obtained, which corresponds to the particular coupling dimen-

sions of the single tool.

Claims

1. A rapid tool coupling device for digger tools, in which a tool is provided with two pivots operating as means for hooking-up, **characterised in that** it comprises:

a body (1) provided with devices for blocking, comprising mobile hooks (2) which are actuated to achieve stable removable couplings with at least one of the two pivots;

at least one plurality of first supports (5) and at least one second support (6), which are predisposed to couple with a corresponding plurality of pairs of the two pivots, which pairs comprise a first pivot (3) and a second pivot (4), and which can be removably fixed to the body (1).

2. The rapid tool coupling device of claim 1, **characterised in that** it comprises a plurality of the first supports (5) and a plurality of the second supports (6) which are predisposed to couple with a corresponding plurality of the first pivots (3) and the second pivots (4) and which are removably fixable to the body (1).

3. The rapid tool coupling device of claim 1 or 2, **characterised in that** the first supports (5) and the second supports (6) are respectively provided with seatings (50 and 60) for contactingly housing the first pivots (3) and the second pivots (4); a pair formed by a first support (5) and a second support (6) corresponding to a single pair, formed by a first pivot (3) and a second pivot (4) equipping a single tool (7).

4. The rapid tool coupling device of claim 1 or 2, **characterised in that** the first supports (5) and the second supports (6) can be constrained to the body (1) in predetermined positions, with removable constraints.

5. The rapid tool coupling device of claim 4, **characterised in that** the removable constraints use same references on the body (1) for all the first supports (5).

6. The rapid tool coupling device of claim 4, **characterised in that** the removable constraints use same references on the body (1) for all the second supports (6).

7. The rapid tool coupling device of claim 5, **characterised in that** the references are constituted by holes (11) made on the body (1) for allowing a con-

nection by bolting of any of the first supports (5) on the body (1).

8. The rapid tool coupling device of claim 6, **characterised in that** the references are constituted by holes (12) made on the body (1) for allowing a connection by bolting of any of the second supports (6) on the body (1).




Fig. 4

Fig. 3





Fig. 2





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 20 4404

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 08, 6 October 2000 (2000-10-06) -& JP 2000 129713 A (SHIN CATERPILLAR MITSUBISHI LTD), 9 May 2000 (2000-05-09)	1	E02F3/36
A	* abstract; figures *	2,3	
X	US 5 549 440 A (CHOLAKON RIFKA ET AL) 27 August 1996 (1996-08-27)	1	
A	* figures 2-12B * * column 10, line 36 - column 11, line 7 * * operaton *	2-4,6,8	
X	US 6 158 950 A (INGRAM GARY ET AL) 12 December 2000 (2000-12-12)	1	
A	* figures 2-8 *		
A	GB 2 330 570 A (MILLER RONALD KEITH ;MILLER GARY (GB); MILLER DOREEN JACQUELINE (G) 28 April 1999 (1999-04-28)	1	
	* figures 6-8,12,13 *		TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	DE 93 19 362 U (MACMOTER SPA) 31 March 1994 (1994-03-31)	1	E02F
	* figures *		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 5 April 2002	Examiner Guthmuller, J
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03 82 (P/0401)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 20 4404

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

05-04-2002

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 2000129713 A	09-05-2000	NONE	
US 5549440 A	27-08-1996	AU 689538 B2 AU 1628595 A CA 2146109 A1	02-04-1998 04-07-1996 29-06-1996
US 6158950 A	12-12-2000	NONE	
GB 2330570 A	28-04-1999	AU 4527199 A EP 1112413 A1 WO 0014342 A1	27-03-2000 04-07-2001 16-03-2000
DE 9319362 U	31-03-1994	DE 9319362 U1	31-03-1994

EPO FORM P449

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82